

20-50-10-13

**Tri-Band Vehicular Antenna** 

30-88 / 225-450 / 1325-1850 MHz

## FEATURES

- Three independent outputs
- Robust, spring mounted element, can be tied down for stowage
- Tested for "Oakbeam" impact survival
- Omni-directional azimuth pattern with radiation maximum near horizon
- DC grounded element with at least 10 KV high voltage protection
- Standard 4 hole NATO mount
- Complies with MIL-STD-810 Environmental and MIL-S-901 Shock

Derived from Cooper Antennas very successful dual band 20-20-13

(AS-4697/VRC) which has been supplied in large quantities to the US Army, this tri-band version adds 1325-1850 MHz capability to a well proven design.

The 20-50-10-13 is a vertically polarized, VHF/UHF/L-band antenna having 35/40 dB filters between each of three RF outputs.

The antenna comprises a UHF dipole surmounted by a stacked L-band dipole integrated within a VHF monopole.

Radiating elements are encased in a high strength, fiber glass tube with filters and matching circuits in the antenna base which has a standard 4 hole NATO mounting plate.

**Cooper Antennas Ltd for non-USA customers** Thames Industrial Estate, Unit K, Fieldhouse Lane, Buckinghamshire SL7 1TB, UK Tel: +44 (0) 1628 482 360 Email: sales@cooperantennas.com www.cooperantennas.com



Australian Representatives ROJONE, PTY LTD. Tel: 02 9829 1555 E: sales@rojone.com.au www.rojone.com.au

Cooper Antennas Ltd is Accredited to: ISO9001, AS9100, ISO14001 and MAA Approved

## SPECIFICATIONS Cooper Antennas Model 20-50-10-13 Tri-band Vehicular Antenna

|                   | ELECTRICAL  |
|-------------------|---|
| Frequency Band    | 30 - 88 MHz<br>225 - 450 MHz<br>1325 - 1850 MHz   |
| Impedance         | 50 ohms (nominal)   |
| VSWR              | ≤ 3.5:1 over 95% of band 30 - 88 MHz<br>≤ 3.0:1 over 95% of band 225 - 450 MHz<br>≤ 2:1 over 95% of band 1325 - 1850 MHz                                |
| Polarization      | Vertical  |
| Gain              | Between –5 dBi and –2.5 dBi over the band 30 - 88 MHz<br>Better than 0 dBi over the band 225 - 450 MHz<br>Typically +2 dBi over the band 1325 - 1850MHz |
| Isolation         | ≥ 35 dB VHF/UHF<br>≥ 40 dB UHF/L-Band<br>≥ 35 dB VHF/L-Band   |
| Power Handling    | 65 Watts CW   |
| Connectors        | BNC Female VHF<br>TNC Female UHF<br>N Type Female L-Band  |
| MECHANICAL        |   |
| Height from Mount | 82 inches (2083 mm) max   |
| Element Diameter  | 2.25 inches (57 mm)   |
| Weight            | 10 lbs (4.55 kg)  |
|                   | FINISH  |

## Lusterless Urethane NATO Green (or Tan as 20-50-10-13F07) Other finish options are available. Please specify finish required when ordering.

Note: Cooper Antennas Ltd has a policy of continuous product improvement and data herein is therefore subject to change. Please check with Cooper Antennas Ltd that this data sheet is at latest issue before initiating contract activity.