



21-50-41
NSN 5985-01-564-6243
Tri-Band ELT
Antenna
121.5, 243 and 406 MHz

FEATURES

- **Covers 121.5, 243 and 406 MHz without tuning**
- **Very lightweight**
- **For helicopter and fixed wing aircraft up to 350 Knots**
- **Glass/Epoxy –Aluminum construction**
- **Small footprint**
- **Meets AS3191 lightning requirements**
- **Designed to DO 160 Environmental conditions**



The 21-50-41 is an externally mounted airborne VHF/UHF antenna operating at the three primary distress frequencies.

A fiberglass rod with an internal element is fitted into an aluminum base which contains foamed-in place matching circuits capable of handling up to 25 Watts power.

The method of construction provides protection from world-wide military environmental conditions including vibration, shock and temperature variations.

Cooper Antennas Ltd for non-USA customers
Thames Industrial Estate, Unit K, Fieldhouse Lane,
Buckinghamshire SL7 1TB, UK
Tel: +44 (0) 1628 482 360
Email: sales@cooperantennas.com
www.cooperantennas.com



Australian Representatives
ROJONE, PTY LTD.
Tel: 02 9829 1555
E: sales@rojone.com.au
www.rojone.com.au

Cooper Antennas Ltd is Accredited to: ISO9001, AS9100, ISO14001 and MAA Approved

SPECIFICATIONS

Cooper Antennas Model 21-50-41 Tri-band ELT Antenna

ELECTRICAL

Frequency Range	121.5, 243 and 406 MHz
Gain (typical)	+ 2dBi typical
VSWR	2.0:1 max @ 121.5 and 243 MHz 1.5:1 max @ 406 MHz
Impedance (nominal)	50 Ohms
Power	25 Watts
Polarization	Vertical
Radiation	Nominally omni directional in azimuth plane
Antenna RF Connector	TNC Female for 121.5 and 243 MHz BNC Female for 406 MHz

MECHANICAL

Construction	Fibreglass whip/ Aluminium base
Height	15.5 inches (394mm)
Weight	0.45 lb (0.20kg)
Base Plate Shape	Tear drop
Fixing Holes	4 x Ø 0.170 inches (4.3mm) ±0.005 inches (0.127mm) holes, counter sunk at 100° Ø 0.325 inches (8.1mm).

FINISH

Antenna	Urethane Gloss White
---------	----------------------

Other finish options are available. Please specify finish required when ordering.

**Note: Cooper Antennas Ltd has a policy of continuous product improvement and data herein is therefore subject to change.
Please check with Cooper Antennas Ltd that this data sheet is at latest issue before initiating contract activity.**