



21-50-46
UHF/MUOS SATCOM
and VHF/UHF LOS Antenna
240 to 385 and 30 to 512 MHz

FEATURES

- **Suitable for helicopter, vehicular, fixed and mobile applications**
- **Covers UHF Satcom and MUOS as well as VHF/UHF Line of Sight (LOS)**
- **All Weather operation**
- **Wide Angle pattern coverage without Hi-Lo switching**
- **200 Watts CW Power handling for Satcom**
- **Designed to MIL-STD-810**
- **Drop on replacement for Chelton 19-440 Series**



Combining highly efficient “droopy dipoles” with a wide band, line-of-sight linear element, the 21-50-46 provides Hi-Lo angle UHF Satcom from a single connector plus a separate VHF/UHF/EPLRS element in a single airborne antenna.

Element shaping and matching of the circularly polarized dipoles provides UHF Satcom coverage right through the UHF and MUOS band with useable radiation and gain typically from zenith down to 20 degrees or less above the horizon.

The robust design is suitable for helicopter and fixed wing aircraft operating up to 450 knots.

Cooper Antennas Ltd for non-USA customers
Thames Industrial Estate, Unit K, Fieldhouse Lane,
Buckinghamshire SL7 1TB, UK
Tel: +44 (0) 1628 482 360
Email: sales@cooperantennas.com
www.cooperantennas.com



Australian Representatives
ROJONE, PTY LTD.
Tel: 02 9829 1555
E: sales@rojone.com.au
www.rojone.com.au

SPECIFICATIONS

Cooper Antennas Model 21-50-46 UHF/MUOS SATCOM and VHF/UHF LOS Antenna

ELECTRICAL

Frequency	Line of Sight (LOS) :	30 - 512 MHz
	Satcom :	240- 385 MHz
Gain (typical)	LOS:	≥ -23 dBi @ 30 MHz ≥ -10 dBi @ 88 MHz ≥ -3 dBi (average) 118 - 174 MHz ≥ 0 dBi to +3 dBi 225 - 512 MHz
	Satcom:	+6.5 dBiC @ Zenith ≥ 0 dBiC @ all elevation angles above +25°.
VSWR	LOS:	30-449 MHz ≤ 2.5:1; 450-512 MHz ≤ 3:1
	Satcom:	≤ 1.75:1
Impedance (nominal)		50 Ohms
Power	LOS :	50 Watts VHF, 200 Watts UHF
	Satcom :	200 Watts
Polarization	LOS:	Linear
	Satcom:	Right Hand Circular (maximum at zenith)
Antenna RF Connector	LOS:	TNC Female
	Satcom:	N Female
Operational Temperature		-54°C to +71°C

MECHANICAL

Overall Height	11.5 inches (292mm) max
Weight	4.8 lbs (2.18kg) max

FINISH

Standard	Urethane Lusterless Grey FED-STD-595 36173
----------	--

Other finish options are available. Please specify finish required when ordering.

Note: Cooper Antennas Ltd has a policy of continuous product improvement and data herein is therefore subject to change.
Please check with Cooper Antennas Ltd that this data sheet is at latest issue before initiating contract activity.