

21-50-62

Multi-Band VHF/UHF, Communications Antenna 30 to 88 MHz, 225 to 400 MHz

FEATURES

- Aero-dynamic design
- Light weight/ high strength
- Fully environmentally sealed
- Internal VHF/UHF filters
- Full 30-88 and 225-400 MHz LOS communications with no tuning required
- SINCGARS & HAVEQUICK compatible.
- Designed to MIL-STD-810
 Environmental Conditions



The 21-50-62 is a rugged multifunction VHF/UHF communications antenna designed for airborne applications. A high strength vertical shell houses 30 - 88 and 225 - 400 MHz linear elements to be used with separate VHF & UHF line of sight "LOS" communications radios. Footprint is compatible with Collins 437S-1H and Chelton 12-437 series antennas. The use of top loading disc optimises the efficiency in the VHF and the antenna provides omni-directional radiation throughout the operating frequency range.

Cooper Antennas Ltd for non-USA customers

Thames Industrial Estate, Unit K, Fieldhouse Lane, Buckinghamshire SL7 1TB, UK

Tel: +44 (0) 1628 482 360

Email: sales@cooperantennas.com

www.cooperantennas.com



Australian Representatives ROJONE, PTY LTD.

Tel: 02 9829 1555 E: sales@rojone.com.au www.rojone.com.au

SPECIFICATIONS

Cooper Antennas Model 21-50-62 Multi-Band, Communications Antenna

ELECTRICAL

Frequency 30-88MHz / 225-400 MHz

Gain ≥ -16 dBi @30 MHz

≥ -7 dBi @88 MHz

≥ +1.5 dBi over 225 - 400 MHz

VSWR ≤ 2.5:1

Impedance (nominal) 50 Ohms

Power 50 Watts (30 – 88 MHz)

100 Watts (225 - 400 MHz)

Polarization Vertical

Isolation 50 dB between ports

Antenna RF Connector UHF: N Female

VHF: TNC Female

MECHANICAL

Height 13 inches max (330 mm)

Mounting Hole 8 x Ø 0.208 - 0.234 inches holes, counter bore Ø 0.39 inch

Weight 6.5 lbs (2.95 kg)

FINISH

Antenna Urethane lusterless Black

Base Plate Unpainted

Other finish options are available. Please specify finish required when ordering.

Note: Cooper Antennas Ltd has a policy of continuous product improvement and data herein is therefore subject to change. Please check with Cooper Antennas Ltd that this data sheet is at latest issue before initiating contract activity.