

1		2	
REVISIONS			
ISS	ZONE	DESCRIPTION	PER REQUEST DATE


3rd ANGLE PROJECTION

THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE, OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.

DO NOT SCALE

A	REVISION	DATE	CHECKED
	A	20110914	L. G.

Heatshrink



Din 7/16 Male

SPECIFICATION for AMA-5247CL-30W-30A

FREQ RANGE:	700-2700MHz
POWER:	30 Watts for Closed Environment
RETURN LOSS:	20dB Typ
IM:	< -150dBc@43dBm x 2
HUMIDITY:	< 95% Non Condensing
OP TEMP:	-40 to +55 °C
CONNECTOR:	716 Din Male
CABLE:	PTFE Silver Plated 50 Ohm Dia 5
SIZE:	260x260x50 Excl. Conn. Approx.

Note:

Load is designed for maximum 10 connects/disconnects only with regard to IM spec. This is not a test load!

Heatshrink Over and Sealed

	ROJONE PTY LTD ACN 002691241 44 AERO RD INGLEBURN 2565 SYDNEY, AUSTRALIA Ph: (612) 9829 1555 Fax: (612) 9605 8812 Web: www.rojone.com.au E-mail: sales@rojone.com.au	TITLE 50 OHM 30W LOAD for TELSTRA AMA-5247CL-30W-30A	
	MATERIAL N/A	DRAWN Y. GU	DRWG No: 001004001037
FINISH N/A	CHECKED	SCALE N/A	SHEET 1 OF 1
APPROVED		FILENAME 001004001037ISSA.DWG	A2

UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES (mm) TOLERANCE: LINEAR ±0.1° ANGULAR ±1° REMOVE ALL BURRS AND SHARP EDGES