



REVISIONS			
ISS	ZONE	DESCRIPTION/PER REQUEST	DATE

3rd ANGLE PROJECTION

THIS DOCUMENT AND THE DESIGN SHOWN THEREON IS THE PROPERTY OF ROJONE PTY LTD AND MUST NOT BE SOLD, LENT, GIVEN AWAY, COPIED, REPRODUCED OR OTHERWISE DIVULGED TO ANY THIRD PARTY OR USED FOR MANUFACTURE, OR ANY OTHER PURPOSE WITHOUT DIRECT WRITTEN PERMISSION OF ROJONE PTY LTD.

DO NOT SCALE

REVISION	DATE	CHECKED
A	20160204	L. B.

Part Number: AMA-5257-200W Series
Description: 200W Low PIM Cable Load

Specification	
FREQ RANGE:	694-2700MHz
POWER MAX.:	200W CW@ 50% duty circle
RETURN LOSS:	20dB Typ
IM:	< -150dBc@43dBm _{x2}
HUMIDITY:	< 95% Non Condensing
OP TEMP:	-40 to +40 °C
CONNECTOR:	See Order Code Selection
SIZE:	167X167X56MM + CONN.
WEIGHT:	0.9 Kg Approx.

Order Code
AMA-5257CL-200W - 30A

CONNECTOR TYPE	
13A	N Male
13C	N Female
30A	716 DIN male
30C	716 DIN Female
45A	4.3-10 Male
45C	4.3-10 Female

NOTE:

1/ Input RF Power 200 Watts Continuous for Max 20 Minutes

2/ Fan version for high duty cycle available

Please consult factory for detail

UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES (mm) TOLERANCE: LINEAR ± 0.1 ANGULAR $\pm 1^\circ$ REMOVE ALL BURRS AND SHARP EDGES

<p>ROJONE PTY LTD ACN 002691241 44 AERO RD INGLEBURN 2565 SYDNEY, AUSTRALIA</p> <p>Ph: (612) 9829 1555 Fax: (612) 9605 8812 Web: www.rojone.com.au E-mail: sales@rojone.com.au</p>	TITLE 200W LOW PIM CABLE LOAD AMA-5257CL-200W-30A	
	DRWG No: 001004001053	
MATERIAL	DRAWN Y. GU	SCALE 1:1 SHEET 1 OF 1
FINISH	CHECKED	FILENAME 001004001053ISSA.DWG
	APPROVED	A4