

## RF DC Block Protector, 2.00 – 6.00 GHz, Type N F-F, 10W, IP67

### DCB-WFI-NFF



#### • DCB-WFI-NFF

N Female Connectors on Surge and Protected Side

The DCB series surge arrester is a RF broadband device designed for surge and lightning protection applications where DC Block is required. A DC Blocking device with its internal series capacitor circuit. This DCB unit offers excellent surge / lightning suppression for telecommunications systems.

The DCB series demonstrates excellent RF characteristics while offering outstanding surge protection.

#### FEATURES:

- Broad Band Design
- Excellent Insertion Loss and Return Loss Characteristics Over Frequency Range
- DC Block
- Multi-Strike Capability
- Max Surge Current of 20kA
- Max Power 10W
- RoHS & CE Compliant
- Bulkhead Mounting (Hex Nut, Lock Washer and O-Ring Included)
- IP67 Rated

#### APPLICATIONS:

- Wi-Fi
- 4G/5G Cellular Systems
- Other Wireless Applications that Require DC Block to Equipment

RF Specifications	
<b>Impedance</b>	50 Ω
<b>Frequency</b>	2.00 – 6.00 GHz
<b>VSWR/Return Loss (Over Frequency)</b>	≤1.25 Max / 19.1 dB
<b>Insertion Loss (Over Frequency)</b>	≤0.2dB Max.
<b>Maximum RF Power</b>	10 Watts

Transient Specifications	
<b>Protection Circuit</b>	DC Block
<b>Surge Current</b>	IEC 61000-4-5 8/20µs Waveform
<b>Maximum Surge</b>	20 kA (1x)
<b>Multi-Strike</b>	10 kA Multiple (10x)
<b>Let-Through Energy</b>	≤10µJ ±20% @ 20kA 8/20µs Waveform
<b>Let-Through Voltage</b>	≤10VDC ±20% @20kA 8/20µs Waveform

**Australian Representatives**  
**ROJONE, PTY LTD.**  
 Tel: 02 9829 1555  
 E: sales@rojone.com.au  
 www.rojone.com.au

## RF DC Block Protector, 2.00 – 6.00 GHz, Type N F-F, 10W, IP67

Mechanical / Environmental Specifications		Material & Finish Specifications		
<b>Storage / Operational Temp</b>	-50°C to +85°C	<b>Component</b>	<b>Material</b>	<b>Finish</b>
<b>Ingress Protection</b>	IP67 IEC 60529	<b>Outer Parts</b>	Aluminum	Ball Burnish
<b>Bellcore</b>	TA-NWT-000487	<b>Connectors</b>	Brass	Tri-Metal
<b>Weight</b>	5.2 oz (147.4 g)	<b>Coupling Nut &amp; Washer</b>	SST	---
<b>RoHS Compliant</b>	Yes	<b>Center Contact</b>	Be Cu / Brass	Gold
<b>CE</b>	Yes	<b>Insulator</b>	PTFE	---

### Mechanical Outlines

