

### **TECHNICAL DATA SHEET**

#### **PRODUCT NAME:**

HSP-1

Two-Way
Communication
Headset



## PRODUCT DESCRIPTION

# High Noise Environment Communications Headset

Rojone headsets are proudly Australian made and are tested and certified with AS/NZS1270-2002, Acoustics – Hearing Protectors. Made with precision, this headset features a field replaceable mic boom and noise cancelling microphone.

The HSP-1 headset features a Nexus TP-120B plug as standard however, other connection configurations are available (see page 3).

#### **PRODUCT APPLICATION**

- · Commercial airlines
- Mining
- Industrial Communications

#### **KEY BENEFITS**

- Clear Communications
- Increased Productivity
- Protects against hearing loss
- Improved working conditions




#### **KEY FEATURES**

- Leather-covered headband
- Olive drab colour
- Noise-cancelling microphone
- -35dB noise reduction
- Lightweight (423 grams)
- ISO 9001:2015 certified manufacturing
- 12 months warranty on headsets

#### **TESTED BY THE NATIONAL ACOUSTIC LABORATORIES TO AS/NZS 1270:2002**

SLC80 Rating31	CLA	SS 5	MASS	6 423g	С	LAMP FORCE 10.4	N
Test Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation	16.0	20.7	30.4	34.8	35.8	39.6	41.8
Standard Deviation	3.5	3.0	3.3	3.8	4.1	3.8	5.3
Mean Minus SD	12.5	17.7	27.1	31.0	31.7	35.8	36.5





#### **TECHNICAL DATA SPECIFICATION**

Model Number	HSP-1		
Style	Headband with leather cover over stainless steel		
	band		
Cups	ABS		
Colour	Olive drab		
Cabling			
Main	Four independently wire lap screened conductors		
	PUR sheath		
Length	900mm, part coiled		
Intercup	Twisted pair, PUR sheath		
Termination	Nexus TP-120B plug		
	(other terminations available)		
Microphone			
Boom	MB-102, Infinitely adjustable, field replaceable		
Element	Noise cancelling electret condenser		
Sensitivity	-71dB +/- 3.5dB @ 1kHz (0dB=1v/µbar)		
Impedance	1.6k Ω +/- 30% @ 1kHz (RI= 2kΩ)		
Response	300 to 4000Hz		
Earphones			
Туре	Dynamic		
Impedance	300 Ω x 2 wired in parallel		
Response	300 to 3500Kz @ 1kHz +/-45Ω		
Weight	423 grams (including standard plug)		
SLC80 Rating	31 (Class 5)		

#### **TERMINATIONS AVAILABLE**

Part Number	Termination	Connector Image
HSP-1-DXC	Lemo Connector	
HSP-1-NM	TP-120B Plug, No Microphone	