

TECHNICAL DATA SHEET

PRODUCT NAME: HSP-5

Two-Way Communication Headset



PRODUCT DESCRIPTION

High Noise Environment Communications Hard Hat Headset

Rojone headsets are proudly Australian-made, tested, and certified with AS/NZS1270-2002, Acoustics—Hearing Protectors. Made with precision, this headset features a fieldreplaceable mic boom and noise-cancelling microphone.

The HSP-5 headset features a TP-120B plug as standard



P: +61 2 9829 1555 E: <u>sales@rojone.com.au</u> W: www.rojone.com.au

44 Aero Road Ingleburn, NSW, 2565 Australia

PRODUCT APPLICATION

- Mining
- Industrial Communications

KEY BENEFITS

- Clear Communications
- Increased Productivity
- Protects against hearing loss
- Improved working conditions




KEY FEATURES

- Leather-covered headband
- Olive drab colour
- Noise-cancelling microphone
- -35dB noise reduction
- Lightweight (423 grams)
- ISO 9001:2015 certified
 manufacturing
- 12 month warranty on headset

TESTED BY THE NATIONAL ACOUSTIC LABORATORIES TO AS/NZS 1270:2002

SLC80 Rating28	CLASS 5		MASS 400g		CLAMP FORCE 11.0N		
Test Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation	15.7	19.5	27.6	30.6	35.0	38.3	46.3
Standard Deviation	4.7	3.2	3.7	3.9	3.7	3.6	4.7
Mean Minus SD	11.0	16.3	23.9	26.7	31.3	34.7	41.6





P: +61 2 9829 1555 E: <u>sales@rojone.com.au</u> W: www.rojone.com.au

44 Aero Road Ingleburn, NSW, 2565 Australia

TECHNICAL DATA SPECIFICATION

Model Number	HSP-5
Style	Hard hat mounting with stainless steel arms and
	resin plastic
Cups	ABS
Colour	Olive drab
Cabling	
Main	Four independently wire lap screened conductors,
	PUR sheath
Length	900mm, part coiled
Intercup	Twisted pair, PUR sheath
Termination	Nexus TP-120B as standard
Microphone	
Boom	MB-102, Infinitely adjustable, field replaceable
Element	Noise cancelling electret condenser
Sensitivity	-71dB +/- 3.5dB @ 1kHz (0dB=1v/µbar)
Impedance	1.6k Ω +/- 30% @ 1kHz (RI= 2kΩ)
Response	300 to 4000Hz
Earphones	
Туре	Dynamic
Impedance	$300 \Omega \times 2$ wired in parallel
Response	300 to 3500Kz @ 1kHz +/-45Ω
Weight	423 grams (including standard plug)
SLC80 Rating	28 (Class 5)

TERMINATIONS AVAILABLE

Part Number	Termination	Connector Image
HSP-5	NEXUS TB-120B	CODDIEC
HSP-5-3.5PMRA	3.5MM STERO R/A PLUG	and the second sec
HSP-5-TA4F-QC	TINI Q-C PLUG	



P: +61 2 9829 1555 E: <u>sales@rojone.com.au</u> W: www.rojone.com.au

44 Aero Road Ingleburn, NSW, 2565 Australia