



## Tunable Vehicular VHF Antenna TA3090M

The TA3090M is a tunable antenna for the 30 to 90 MHz frequency band. This low profile antenna can be tuned by remote control to use the optimum matching circuitry at the required frequency. It thus provides superior gain performance over traditionally matched wideband antennas. Its extremely fast tuning ability (based on PIN diode switching technology) makes the antenna suitable for most of the conventional modulation types.

• Low profile antenna with superior gain performance. Gives up to 6dB better gain compared to a traditional passively matched antenna of same size

• Fast tuning to a new frequency band allows the antenna to be used in different kind of applications

· Supports also wide transmission bandwidths

| Product details*  |   |  |
|-------------------|---|--|
| Frequency range   | 30 - 90 MHz                             |  |
| Matching          | PIN diode based active matching         |  |
| Polarization      | Nominally vertical                      |  |
| Antenna type      | Monopole (ground plane required)        |  |
| Radiation pattern | Omnidirectional                         |  |
| Gain              | Measured patterns on request            |  |
| VSWR              | $\leq$ 3.5 (on tuned band)              |  |
| Nominal Impedance | 50 Ω                                    |  |
| Power rating      | 50 W                                    |  |
| Power supply      | 24 VDC, 5 W (average)                   |  |
| Tuning speed      | < 30 µs (more details on request)       |  |
| Standard color    | Black                                   |  |
| Radiator          | Steel whip with shock absorption spring |  |
| Height            | 2000 mm                                 |  |
| Weight            | 3.0 kg                                  |  |

| Installation*     |  |  |
|-------------------|--|--|
| RF connection     | Female N-type connector                                  |  |
| Power and control | Circular MIL connector (more details on request)         |  |
| Mounting          | 4 hole NATO / US pattern mount (more details on request) |  |

\* Specific adjustments on request

| Order number |                                |             |
|--------------|--------------------------------|-------------|
| TA3090M      | Antenna as described above     | XA          |
| ATA3090M     | Antenna with autonomous tuning | $\Delta X $ |
|              | (see separate data sheet)      | $/$ $\land$ |



Page 1/1